



Elite-790

齐聚物 · 单体 · 光引发剂 · 助剂

免责声明

All products in the text marked with are trademarks of the U-sunny .The information on product specifications provided herein is only binding to the extent confirmed by U-sunny in a written Sales Agreement. U-sunny expressly disclaims any responsibility for the suitability of the products for any specific or particular purposes intended by the user .Suggestions or the use and application of the products and guide formulations are given for information purposes only and without commitment. Such suggestions do not release U-sunny customers from testing the products as to their suitability for the customers intended processes and purposes. U-sunny does not assume any liability or risk involved in the use of its products as the conditions of use are beyond its control. The user of the products is solely responsible for compliance with all laws and regulations applying to the use of the products。including intellectual property rights of third parties.

Elite 790 润湿流平剂

聚硅氧烷-聚醚共聚物

Polymer solids % by weight : 100%

Colour, Gardner: 1

Viscosity at 25℃,cPa.s : 350

Density,g/cm³: 1.02

特性：适用于水性、辐射固化和溶剂型体系。强烈降低表面张力，不影响重涂性具有一定的抑泡能力。提升涂层光泽和丰满度、无雾影产生。

应用：低极性塑料基材涂层，金属、玻璃等无机材料水性体系，辐射固化丝网印刷体系。

推荐用量：0.1-0.5%

储存运输 本品为非危险品，用后容器应严格密封，本品使用有效期为24个月。